



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) **EP 0 998 875 A1**

(12)

**EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

(43) Date of publication:  
10.05.2000 Bulletin 2000/19

(51) Int. Cl.<sup>7</sup>: **A61B 5/05**

(21) Application number: 99921216.0

(86) International application number:  
PCT/JP99/02671

(22) Date of filing: 21.05.1999

(87) International publication number:  
WO 99/60925 (02.12.1999 Gazette 1999/48)

(84) Designated Contracting States:  
DE FR GB

(72) Inventor: **SAKAI, Nobuya**  
Itabashi-ku, Tokyo 174-0063 (JP)


(30) Priority: 25.05.1998 JP 14247998  
12.05.1999 JP 13193299

(74) Representative:  
**Müller-Boré & Partner**  
Patentanwälte  
Grafinger Strasse 2  
81671 München (DE)

(71) Applicant: **TANITA CORPORATION**  
Tokyo 174-0063 (JP)

(54) **BODY FAT METER WITH STATURE MEASURING INSTRUMENT**

(57) An improved body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity can obtain accurate and stable in-vivo impedance even if hand electrodes are used for the measurement. The apparatus includes a body-height measuring device having a footstool on which an examinee mounts, a measuring terminal to contact with the top of examinee's head, and a cursor movable in upward and downward direction with holding said measuring terminal, and also includes in-vivo impedance measuring electrodes integrated with said cursor, wherein said measuring electrodes are located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device contacts with the top of examinee's head so that the angle between torso region and arm region of an examinee becomes approximately right angle when the examinee grasps said measuring electrodes.



EP 0 998 875 A1

## Description

### Technical Field

[0001] The present invention relates to a body-fat measuring apparatus measuring in-vivo impedance and computing body-fat quantity, more especially to a body-fat measuring apparatus equipped with a body-height measuring device.

### Background Art

[0002] In the conventional way for a body-fat measuring apparatus for measuring in-vivo impedance and computing body fat quantity, many measuring devices are proposed such as a device using a body-weight measuring device and hand/foot electrodes disclosed in Japanese Patent Publication No.5-49050 and Japanese Laid-Open Publication No. 7-12635, a device using movable hand electrodes disclosed in Japanese Patent Publication No.7-51242, a device using a body-weight measuring device and foot electrodes with a body-height measuring device disclosed in Japanese Patent Laid-Open Publication No.7-100122.

[0003] When examinee's in-vivo impedance is measured by hand electrodes, it needs to keep examinee's arm region approximately at right angle to his/her torso region so as to obtain a measurement value stably, and also needs to keep the angle same in each measurement especially for assuring the same measured quantity for every measurements. Accordingly, in the body-fat value measuring devices using hand electrodes, it is conventionally suggested to secure the hand electrode elements at a predetermined position, such as Japanese Laid-Open Publication No. 7-12635, or to keep examinee's arm region at right angle to his/her torso region himself/herself by examinee's visual adjustment, such as Japanese Patent Publication No.7-51242. However, in a type of device that the electrode elements are secured at a predetermined position, the device is not capable of adjusting difference in examinee's body height so that the difference in angle between torso region and arm region may be extremely increased to result in making a measured value incorrect upon some examinees' measurement. On the other, in case that examinee identifies and keeps being in right angle by examinee's visual adjustment, the angle is changed in each measurement to result in making a measured value unstable.

[0004] It is accordingly an object of the present invention to solve the above problem and to provide a device capable to obtain accurate and stable in-vivo impedance with hand electrodes, and also to provide a device for effectively utilizing in-vivo impedance measured accurately with the hand electrodes.

### Disclosure of Invention

[0005] For solving the above problem, the present invention provide a body-height measuring device including a footstool on which a examinee mounts, a measuring terminal to contact with the top of examinee's head, and a cursor movable in upward and downward direction with holding the measuring terminal, and also provide in-vivo impedance measuring electrodes integrated with the cursor, whereby the measuring electrodes can be located at the same position in each measurement.

[0006] Furthermore, the in-vivo impedance measuring electrodes integrated with the cursor are located at a height approximately corresponding to the examinee's shoulder as the measuring terminal contacts with the top of examinee's head, whereby the angle between torso region and arm region of an examinee may be approximately right angle when the examinee grasps the measuring electrodes, in most case.

[0007] Examinee's body-height has wide difference. Since the difference between examinees in shoulder height is approximately equal to the difference of their body-height, it is assumable that the difference in shoulder height is a few ten centimeters. Thereto, the difference in height from shoulder to top of head is considerably smaller than the difference in body-height, and its individual difference is a few centimeters.

[0008] If the body-height measuring terminal of the body-height measuring device is contacted with top of head, the hand electrodes is set up so as to be located at shoulder height of a person who is average in body height so that an angle between arm region and torso region may become approximately right angle when most examinees grasp the hand electrodes, and the hand electrodes may be always set up to the same angle in every measurements when the examinee is a same person.

[0009] According to another aspect of the present invention, the apparatus of the present invention further comprises foot electrodes to contact with bottom of an examinee's foot when he/she mounts on the footstool used for body-height measurement, wherein high-frequency current applying paths and potential difference measuring areas are switched over by a controller to collect useful data for computing such as quantity of fat in each of the measuring areas.

[0010] According to further aspect of the present invention, a platform of a body-weight measuring device is used as the footstool in order to enable a single apparatus to measure body-height, in-vivo impedance, and body-weight by a series of operations.

[0011] As the result, the present invention will provide an improved apparatus to collect all of body-height, body-weight, and in-vivo impedance, that result from in-vivo impedance measurement and are included among factors such as examinee's sex, age, body-height, body-weight, and in-vivo impedance, conventionally

applied to an arithmetic expression for computing a body-fat quantity, by a series of operations of a single device.

[0012] With reference to the accompanying drawings, a preferred embodiment of the present invention will be described in detail.

#### Brief Description of the Drawing

[0013]

FIG.1 is a perspective view illustrating the body-fat measuring apparatus equipped with a body-height measuring device showing as an embodiment according to the present invention.

FIG.2 is a block diagram illustrating an example of the circuitry of the body-fat measuring apparatus equipped with a body-height measuring device shown in Fig.1.

#### Best Mode for Carrying out the Invention

[0014] With reference to Fig.1, in the body-fat measuring apparatus equipped with a body-height measuring device as one embodiment according to the present invention, a platform 2 of a body-weight measuring device 1 is used as a footstool of a body-height measuring device 4 to which a columnar support 9 is fixedly attached at one of its edge side. In-vivo impedance measuring foot electrodes 3 with which the bottom of examinee's foot is contacted when the examinee mounts on there, an input device 11 setting up a power source, an information entry of personal data, and an information entry of electrode(s) to be used, and a display device 12 indicating measured or computed result(s) are provided on the surface area of the platform.

[0015] When a determination of the setting up is appointed after the information entry, such as personal data and electrode(s) to be used, with the input device have been completed, the body-weight measuring device is reset to a zero load condition for standby.

[0016] A body-height measuring device cursor 5 that slides along the columnar support 9 in upward and downward direction includes a pair of arms 6 disposed at both of right side and left side respectively, each of the arms having a grip portion at its front edge. Each of the right and left arms is made in the telescopic construction that can be expanded and contracted corresponding to the length of an examinee's arm when the examinee grasps the grip portion, and the telescopic front edge portion is swingably connected to a rear edge of the cursor through a swingable connection portion 13, the telescopic front edge portion being normally used in a specific predetermined position and also being used in flip-up motion when a examinee mounts on the platform.

[0017] An attachment member 7 connects each

upper portion of the arms. A body-height measuring terminal 8 to contact with the top of examinee's head is disposed substantially in the middle of the attachment member. Hand electrodes 10 for measuring in-vivo impedance are disposed at the grip portion of each of right and left arms.

[0018] The relationship among the level of the body-height measuring terminal 8, the level of a measuring sensor (not shown) where the cursor 5 contacts with the columnar support 9 and the level of hand electrodes 10 for measuring in-vivo impedance is constantly kept in a specific relationship. The specific relationship is set up so as to make the angle between torso region and arm region of an examinee approximately right angle when the body-height measuring terminal is contacted with the top of examinee's head and the examinee grasps the hand electrodes, that is, the hand electrodes 10 for measuring in-vivo impedance is set up approximately at the height of the examinee's shoulder.

[0019] An operation process of the body-fat measuring apparatus equipped with a body-height measuring device is described as follows. An examinee enters information of physical features, such as age, sex, and electrode(s) to be used into the input device 11, and then appoints a determination of the setting up by pressing the input device 11 again to make the apparatus a standby condition after the information entry.

[0020] In a automatic body-height measuring device, when the examinee mounts on the right and left foot electrodes 3,3 on the upper surface of the footstool with his/her bare feet with positioning the columnar support 9 of the body-height measuring device at the rear of his/her back, the cursor 5 located at upper portion of the columnar support is automatically started to be descended, and the cursor is continued to be descend until the body-height measuring terminal 8 will be contacted with the top of the examinee's head. When the terminal is contacted with the top of his/her head, a sensor (not shown) disposed in the terminal detects that the terminal is contacted with the top of his/her head so that the descent of the cursor may be stopped and also the in-vivo impedance measuring hand electrodes 10,10 may be stopped at the height of his/her shoulder, and at this moment the preparation for body-height and body-weight measurement is completed.

[0021] Since the angle between arm region and torso region of the examinee becomes approximately right angle when the examinee grasps the in-vivo impedance measuring electrodes disposed in front of the examinee's shoulder with both hands, his/her in-vivo impedance is measured when the electrodes are properly grasped.

[0022] The examinee's body-height, body-weight, and in-vivo impedance are sequentially measured, and these measured values and pre-entered information such as sex and age are then applied to an arithmetic expression to compute fat quantity, etc., The measured results and the computed result(s) are then sequentially

indicated on the display device 12. When every measured value and computed result(s) have been finished to indicate, a signaling device (shown in Fig. 2) then informs the completion of the measurement and computation, at this moment the process is completed.

[0023] The measurement of body-height is started just after the body-height measuring terminal is contacted with the top of the examinee's head even if the examinee does not grasp the hand electrodes, and also the measurement of body-weight is started when the examinee stops his/her motion on the platform and the apparatus then determines that the body-weight measurement can be performed without trouble even if the examinee does not grasp the hand electrodes.

[0024] In a manual type body-height measuring device, when a examinee who mounts on the platform pulls down the hand electrodes of the cursor located upper position of the columnar support, the sensor in the terminal detects that the top of the examinee's head contacts with the terminal to inform the contact with a signal unit such as buzzer sound. When the examinee stops to pull down the hand electrodes responsive to the signal, the measurement of body-height, body-weight, and in-vivo impedance is started.

[0025] A processor (cf. control, computation and memory device shown in Fig.2) performs an operation by use of the arithmetic expression and the information such as examinee's physical data and electrode(s) to be used which was entered from the input device, the body-weight data that was measured by the body-weight measuring device, the body-height data that was measured by the body-height measuring device, and the in-viva impedance data that was measured by the in-viva impedance measuring device, and then indicates the measured body-height, the measured body-weight, the computed body-fat quantity, etc. by the display device 12.

[0026] With reference to Fig.2, the switching circuitry of the electrode(s) to be used for measurement of the in-viva impedance measuring device is described.

[0027] According to Fig. 2, the reference numerals 101, 201, 102, and 202 indicate the hand electrodes 10 that may be contacted with examinee's palms when he/her grasps them by both hands in Fig. 1, and the reference numerals 103, 203, 104, and 204 indicate the foot electrodes that may be contacted with bottom of examinee's foot when he/she mounts on the platform in Fig. 1.

[0028] The reference numerals 101, 102, 103, and 104 indicate electrodes for applying high frequency electric current, and the reference numerals 201, 202, 203, and 204 indicate electrodes for measuring potential difference.

[0029] A switching device (a) and a switching device (b) switch the high frequency current applying electrodes to a high frequency electric current source associated with an output current detecting unit in order to select a current path, and a switching device (c) and a switching device (d) switch the potential difference

measuring electrodes to a potential difference detecting device associated with an A/D converting device in order to select potential difference measuring areas.

[0030] When the high frequency current applying electrodes 101 and 102, and the potential difference measuring electrodes 201 and 202 are respectively selected, the impedance of the examinee's upper body is measured. When the high frequency current applying electrodes 103 and 104, and the potential difference measuring electrodes 203 and 204 are respectively selected, the impedance of the examinee's lower body is measured. The fat quantity is presumed on the basis of each of the measured in-vivo impedance values.

[0031] In such apparatus according to the present invention that includes hand electrodes being respectively contacted with both of the examinee's palms and foot electrodes being respectively contacted with both of bottoms of the examinee's feet so as to enable respectively to collect accurate in-vivo impedance values, the in-vivo impedance of the examinee's left foot is measured when the high frequency current applying electrodes 103 and 104, and the potential difference measuring electrodes 201 and 203 are respectively selected, and the in-vivo impedance of the examinee's right foot is also measured when the high frequency current applying electrodes as same as the above, and the potential difference measuring electrodes 201 and 204 are respectively selected. Thus, the difference between the muscle quantities of the examinee's right and left feet can be learnt by means of switching the potential difference measuring electrodes with using the same current path so that the degree of progress of the rehabilitation on bone fracture may be checked.

[0032] Additionally, the in-vivo impedance of the examinee's torso is measured when the high frequency current applying electrodes 101 and 103, and the potential difference measuring electrodes 202 and 204 are respectively selected so that the amount of fat in abdominal region as being a very important factor for health management can be accurately measured.

#### Effect of the Invention

[0033] When the body-height measuring terminal is contacted with the top of examinee's head and the preparation for the body-height measurement is completed, the angle between torso region and arm region of an examinee becomes approximately right angle when the examinee grasps the in-vivo impedance measuring electrodes by his/her both hands and also each measurement can be performed with the same angle so that accurate and stable measured value can be obtained at all times.

[0034] Furthermore, since the foot electrodes and hand electrodes can be selectively switched to perform accurate measurement for different body regions, fat quantity of each body region can be measured efficiently and accurately.

[0035] Additionally, since the hand electrodes are disposed at the existing cursor of the body-height measuring device, any additional securing device for the hand electrodes is unnecessary.

#### Claims

1. A body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity comprising:

a body-height measuring device including

- (1) a footstool on which a examinee mounts,
- (2) a measuring terminal to contact with the top of examinee's head, and
- (3) a cursor movable in upward and downward direction with holding said measuring terminal,

and in-vivo impedance measuring electrodes integrated with said cursor, whereby iv-vivo impedance is measured when the examinee grasps said electrode by hand.

2. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 1, wherein said in-vivo impedance measuring electrodes are located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device contacts with the top of examinee's head.

3. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 1, wherein said in-vivo impedance measuring electrodes are swingable to said cursor.

4. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 1, wherein said footstool of said body-height measuring device is a platform of a body-weight measuring device.

5. A body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity comprising:

(A) a body-height measuring device including

- (1) a footstool on which a examinee mounts,
- (2) a measuring terminal to contact with the top of examinee's head, and
- (3) a cursor movable in upward and downward direction with holding said measuring terminal,

(B) hand electrodes integrated with said cursor,  
(C) foot electrodes integrated with said footstool, and  
(D) a control device for computing in-vivo impedance with said hand electrodes and said foot electrodes.

6. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein said in-vivo impedance measuring electrodes are located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device contacts with the top of examinee's head.

7. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein said in-vivo impedance measuring electrodes is swingable to said cursor.

8. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein said footstool of said body-height measuring device is a platform of a body-weight measuring device.

9. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein said control device includes a switching means for switching the connection of said hand electrode and said foot electrode.

10. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 1 or claim 2, said in-vivo impedance measuring hand electrodes integrated with said cursor of said body-height measuring device comprise two sets of electrodes to contact with each of palms of right and left hand of the examinee respectively.

11. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 1 or claim 5, wherein said in-vivo impedance measuring electrode integrated with said cursor comprise a pair of electrodes consisting of a high frequency current applying electrode and a potential difference measuring electrode.

12. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein foot electrodes integrated with said footstool of said body-height measuring device comprise two sets of foot electrodes to contact with each of bottoms of right and left feet respectively.

13. A body-fat measuring apparatus equipped with a body-height measuring device according to claim 5, wherein foot electrodes integrated with said foot-

stool of said body-height measuring device comprise a pair of electrodes consisting of a high frequency current impressing electrode and a potential difference measuring electrode.

5

14. A body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity comprising:

(A) a body-height measuring device including 10

- (1) a footstool on which a examinee mounts,  
(2) a measuring terminal contacted with the top of examinee's head, and 15  
(3) a cursor

(a) movable in upward and downward direction with holding said measuring terminal, and 20

(b) located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device contacts with the top of examinee's head. 25

(B) hand electrodes integrated with said cursor,  
(C) foot electrodes integrated with said footstool, and 30  
(D) a control device

- (a) for switching and connecting electrodes applied to said hand electrodes and said foot electrodes, and 35  
(b) for computing in-vivo impedance.

15. A body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity comprising: 40

(A) a body-height measuring device including

- (1) a footstool on which a examinee mounts, 45  
(2) a measuring terminal to contact with the top of examinee's head, and  
(3) a cursor

(a) movable in upward and downward direction with holding said measuring terminal, and 50

(b) located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device is contact with the top of examinee's head. 55

(B) hand electrodes

- (1) including a pair of electrodes consisting of a high frequency current applying electrode and a potential difference measuring electrode integrated with said cursor, and  
(2) having two sets of said pair of electrodes to independently contact with each of palms of both hands.

(C) foot electrodes

- (1) including a pair of electrodes consisting of a high frequency current applying electrode and a potential difference measuring electrode integrated with said footstool, and  
(2) having two sets of said pair of electrodes to independently contact with each of bottoms of both feet, and

(D) a control device for controlling switching of said hand electrodes and said foot electrodes, and computing in-vivo impedance.

16. A body-fat measuring apparatus for measuring in-vivo impedance and computing body-fat quantity comprising:

(A) a body-height measuring device including

(1) a footstool on which a examinee mounts

(a) being a platform of a body-weight measuring device,

- (2) a measuring terminal to contact with the top of examinee's head, and  
(3) a cursor

(a) movable in upward and downward direction with holding said measuring terminal, and

(b) located at a height approximately corresponding to the examinee's shoulder as said measuring terminal of said body-height measuring device contacts with the top of examinee's head.

(B) hand electrodes

- (1) including a pair of electrodes consisting of a high frequency current applying electrode and a potential difference measuring electrode integrated with said cursor, and  
(2) having two sets of said pair of elec-

trodes to independently contact with each of palms of both hands.

(C) foot electrodes

5

(1) including a pair of electrodes consisting of a high frequency current applying electrode and a potential difference measuring electrode integrated with said footstool, and

10

(2) having two sets of said pair of electrodes to independently contact with each of bottoms of both feet, and

(D) a control device for controlling switching of 15  
to said hand electrodes and said foot electrodes, and computing in-vivo impedance.

20

25

30

35

40

45

50

55

FIG. 1







FIG. 2



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP99/02671

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> Int.Cl. <sup>6</sup> A61B5/05  According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) Int.Cl. <sup>6</sup> A61B5/05  Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1926-1999 Toroku Jitsuyo Shinan Koho 1994-1999 Kokai Jitsuyo Shinan Koho 1971-1999 Jitsuyo Shinan Toroku Koho 1996-1999  Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP, 7-303617, A (Fujitsu Ltd.), 21 November, 1995 (21. 11. 95), Fig. 3 (Family: none)	1, 3-5, 7-13
Y	JP, Microfilm of the specification and drawings annexed to the request of Japanese Utility Model Application No. 48-143517 (Laid-open No. 50-86091) (Otoya Kogyo K.K.), 22 July, 1975 (22. 07. 75), Fig. 1 (Family: none)	1, 3-5, 7-13
Y	JP, Microfilm of the specification and drawings annexed to the request of Japanese Utility Model Application No. 60-41188 (Laid-open No. 61-156906) (K.K. Zena), 29 September, 1986 (29. 09. 86), Fig. 10 (Family: none)	1, 3-5, 7-13
Y	JP, 7-12635, A (YAMAN Ltd.), 17 January, 1995 (17. 01. 95), Fig. 1 (Family: none)	4, 5, 7-13
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family		
Date of the actual completion of the international search 16 June, 1999 (16. 06. 99)		Date of mailing of the international search report 29 June, 1999 (29. 06. 99)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP99/02671

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP, 9-285455, A (Omron Corp.), 4 November, 1997 (04. 11. 97), Full text (Family: none)	1-16
A	JP, 7-75625, A (K.K. Akatsuki Denki Seisakusho), 20 March, 1995 (20. 03. 95), Full text (Family: none)	1-16
A	JP, 6-304149, A (Matsushita Electric Works, Ltd.), 1 November, 1994 (01. 11. 94), Full text (Family: none)	1-16
A	JP, 7-100122, A (Tanita Corp.), 18 April, 1995 (18. 04. 95), Full text & EP, 545014, B1 & US, 5415176, A	1-16
A	JP, CD-ROM of the specification and drawings annexed to the request of Japanese Utility Model Application No. 3-27050 (Laid-open No. 5-51304), U (Tanita Corp.), 9 July, 1993 (09. 07. 93), Full text (Family: none)	1-16
A	JP, 6-189928, A (Sekisui Chemical Co., Ltd.), 12 July, 1994 (12. 07. 94), Full text (Family: none)	1-16

Form PCT/ISA/210 (continuation of second sheet) (July 1992)